



## HUSQVARNA 135R

Versatile brushcutter, perfect for homeowners. Easy starting with Auto-return stop switch and fuel pump. The X-Torq® engine provide raw power and excellent fuel economy. Comes with double harness, easy loading semi automatic trimmer head and grass knife.



### X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



### Adjustable handle bar

Adjustable and ergonomically designed handlebar for best comfort.

### Standard double harness

Standard harness for lighter brushcutters.



### Tap 'n Go

Heavy duty twin line cutting system with Tap 'n Go for quick line feed.



## FEATURES

- Standard harness for lighter brushcutters
- Adjustable handle bar for best comfort
- X-Torq® engine cuts emission and fuel consumption
- Easy to use trimmer head
- Air purge for easier cold starting
- Auto return stop switch for easy starting
- Versatile use with combi guard
- Grass bevel gear for best cutting performance
- Comfortable handle design

Technical Specifications	
<b>CAPACITY</b>	
Clutch engagement speed (±120)	3800 rpm
Idling speed	2900 rpm
Maximum power speed	8400 rpm
Maximum rpm output shaft	8220 rpm
Power output	1.4 kW
Torque, max.	1.8 Nm
Torque, max. at rpm	6600 rpm
<b>CERTIFICATIONS</b>	
#Approved according to CE	Yes
Cert machine dir. 2006/42/EC Decl. No.	Yes
<b>DIMENSIONS</b>	
Article gross weight	11806 g
Article net weight	8960 g
Cutting width	47 cm
Tube diameter	28 mm
Tube length	1483 mm
Weight (excl. cutting equipment)	6.8 kg
<b>ENGINE</b>	
Cylinder bore	38 mm
Cylinder displacement	34.6 cm <sup>3</sup>
Cylinder stroke	30.5 mm
Electrode gap	0.5 mm
Engine Family CARB	LHVXS.0354EE
Engine Family EPA	LHVXS.0354EE
Gear ratio	1
Ignition module air gap	0.3 mm
Spark plug	Champion RCJ6Y
<b>EQUIPMENT</b>	
Drive gear angle	35 °
OEM Grass blade	Multi 300–3
OEM Harness	Standard double harness
OEM Trimmer head	T35 M12
<b>LUBRICANTS</b>	
Fuel consumption	435 g/kWh
Fuel tank volume	0.6 l
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Lubricant type (bevel gear)	Mineral grease
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	1070 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>PACKAGING</b>	
Packaging height	310 mm
Packaging length	1850 mm
Packaging volume	189.255 dm <sup>3</sup>
Packaging width	330 mm
Pallet layers	6
Quantity in Master pack	1
<b>EMISSION DATA CARB</b>	
Engine Family CARB	LHVXS.0354EE
Exhaust emissions (CO average)	243.69 g/kWh
Exhaust emissions (CO average)	1029 g/kWh
Exhaust emissions (HC average)	29.31 g/kWh
Exhaust emissions (NOx average)	1.09 g/kWh
<b>EMISSION DATA EPA</b>	
Exhaust emissions (CO average)	243.69 g/kWh
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (CO average)	1029 g/kWh
Exhaust emissions (HC average)	29.31 g/kWh

Technical Specifications	
Exhaust emissions (NOx average)	1.09 g/kWh
<b>EMISSION DATA EU</b>	
Exhaust emissions (CO average)	418.31 g/kWh
Exhaust emissions (CO average)	862 g/kWh
Exhaust emissions (CO2 EU V)	862 g/kWh
Exhaust emissions (HC average)	40.51 g/kWh
Exhaust emissions (NOx average)	0.46 g/kWh
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	113 dB(A)
Sound power level, measured	112 dB(A)
Sound pressure level at operators ear	98 dB(A)
<b>VIBRATIONS</b>	
Daily Vibration (Aeqv)	2.9 m/s²
Daily Vibration Exposure (A8)	1.9 m/s²
Daily Vibration Time (Time factor)	3.5 h
Equivalent vibration level (ahv, eq) left handle	2.9 m/s²
Equivalent vibration level (ahv, eq) right handle	2.5 m/s²