



HUSQVARNA 520iRX

A lightweight and high performance bullhorn trimmer for professional users. Perfect for gardeners, landscapers and contractors. Features excellent ergonomics and balance, 2-way rotation trimmer head and long-lasting brushless motor. Comfortable harness included.



Efficient brushless motor

Our in-house developed, advanced brushless motor is 25 % more efficient than a standard brush motor. This means that the motor provides a high and consistent torque – even when you cut high, thick or wet grass.




Battery through body design (Pat.pend.)

Smart battery pack position, placed horizontally through the body of the machine. Reduces the risk of having dirt, chips, dust and water accumulate in the battery compartment, causing connector issues. Also, it means the weight of the battery can be placed in or near the desired center of gravity and in the rotational axis of the product, resulting in increased maneuverability. The through body design also offers a high degree of flexibility since it allows battery packs of different sizes to be used.

Dual direction

The rotational direction of the trimmer head can be changed for less grass on walk ways.



High handle bar

High handle bar increases freedom of movement when working on slopes.



FEATURES

- Dual direction, less grass on walk ways
- Smart battery pack position, placed horizontally through the body of the machine.
- Efficient brushless motor
- High handle bar, more leg space
- Weatherproof (IPX4) - Use in all weather conditions
- Comfortable padded harness
- Lightweight and well balanced
- Intuitive keypad
- Maximum runtime
- Allows you to quickly switch the same battery between different product applications and keep working.
- Choose savE™ mode for maximum runtime
- Silent operation
- Easy to use trimmer head
- Low maintenance

Technical Specifications	
BATTERY	
Battery type	Li-Ion
Battery voltage	36 V
Weight without battery	3.8 kg
DIMENSIONS	
Cutting width	40 cm
Tube diameter	24 mm
Tube length	970 mm
Weight without battery	3.8 kg
ENGINE	
Motor type	BLDC (brushless)
EQUIPMENT	
OEM Harness	Balance 35B
OEM Trimmer head	T25B
LUBRICANTS	
Power/fuel type	Battery
PACKAGING	
Packaging height	291 mm
Packaging length	1850 mm
Packaging volume	113.59 dm ³
Packaging volume	0.114 m ³
Packaging width	211 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	96 dB(A)
Sound power level, measured	92 dB(A)
Sound pressure level at operators ear	76.1 dB(A)
VIBRATIONS	
Daily Vibration (Aeqv)	0.8 m/s ²
Daily Vibration Exposure (A8)	0.7 m/s ²
Daily Vibration Time (Time factor)	3.0 h
Equivalent vibration level (ahv, eq) left handle	1.2 m/s ²
Equivalent vibration level (ahv, eq) right handle	0.7 m/s ²